



## DSR701-RECESSED/SURFACE

- Installed post-production to fix warped doors.
- Must run complete height of door.
- Can be partially recessed or surface mounted to the back of the door.
- ±10mm adjustment can be made from the top of the door with a M4 Allen Key (not included).
- Min. door thickness 5/8" (16 mm).
- Requires M4 (U.S. #8) flathead wood countersunk screws for partially recessed installation or wood panhead screws for surface installation.
- Can be cut from the bottom up to 15-3/4" (400 mm).
- Note: Sold in Boxes of 10 sets.



## DSR213-RECESSED

- Installed at time of production to prevent door from warping.
- Adjustors installed 2-3/8" (60 mm) from the top and bottom of the door.
- Partially Recessed Door Straightener with Cover Caps.
- ±10 mm adjustment can be made from the back of the door with a M8 slot wrench (included).
- Min. door thickness 5/8" (16 mm).
- Requires 8 M4 (U.S. #8) flathead contersunk wood screws for installation.
- Note: Sold in Boxes of 25 sets.



Box (sets)	Materials	Finish
25	Rod: Steel,	Plain
	Adjuster: Zinc	Nickel
	Covers: PVC Plastic, PPT Plastic	White, Black

Item No.	Min. Door Thickness	Adjust (mm)	Length Min-Max (A)	Box (sets)	Materials	Finish
DSR701-1830/B-10	5/8"	± 3/8"	56-5/16"~72-1/16"	10	Rod: Steel Casing: Aluminum	Black
DSR701-1830/S-10						Silver
DSR701-2200/B-10			Black			
DSR701-2200/S-10			Silver			

Item No.	Min. Door Thickness	Adjust	Center Distance (A)	Door Length
DSR213-1524-25	5/8"	± 3/8"	43-7/16" ~ 60"	48-3/16" ~ 64-3/4"
DSR213-1930-25			59-7/16" ~ 76"	64-3/16" ~ 80-11/16"
DSR213-2330-25			75-3/16" ~ 91-3/4"	79-15/16" ~ 96-7/16"
DSR213-2700-25			89-3/4" ~ 106-5/16"	94-1/2" ~ 111"